LISTING OF THE CLAIMS

Pursuant to 37 C.F.R. §1.121, provided below is a listing of the claims of the present patent application.

1. (Currently Amended) An increment/decrement circuit for use with a general purpose performance counter ("GPPC") connected to a bus carrying debug data, the increment/decrement circuit comprising:

a delay circuit block operable to receive and align at least a multi-bit block of said debug data;

a first mask circuit connected to said delay circuit block, wherein said first mask circuit is operable to select a first portion of said <u>aligned</u>, <u>multi-bit</u> block of <u>aligned</u> debug data; for incrementing;

a second mask circuit connected to said delay circuit block, wherein said second mask circuit is operable to select a second portion of said <u>aligned</u>, <u>multi-bit</u> block of <u>aligned</u> debug data; for decrementing; and

an accumulation circuit connected to said first mask circuit and said second mask circuit, said accumulation circuit for

PATENT APPLICATION

DOCKET NO.: 200208998-1

generating an accumulated value using said first portion and said

second portion. based on outputs provided by said first and

second mask circuits.

2. (Currently Amended) The increment/decrement circuit as

recited in claim 1, wherein said <u>multi-bit</u> block of said debug

data comprises 16 bits.

3. (Currently Amended) The increment/decrement circuit as

recited in claim 1, wherein said multi-bit block of said debug

data forms a portion of an 80-bit wide debug data signal.

4. (Currently Amended) The increment/decrement circuit as

recited in claim 1, wherein said delay circuit block is operable

responsive to a delay values signal that provides clock delaying

values for each bit in said multi-bit block of said debug data.

7

- 5. (Original) The increment/decrement circuit as recited in claim 1, wherein said delay circuit block includes a series of registers operable to be tapped for providing a plurality of inputs to a Multiplexer (MUX) block that is controlled by a delay_values signal.
- 6. (Currently Amended) The increment/decrement circuit as recited in claim 1, wherein said first mask circuit comprises an AND block having a plurality of 2-input AND gates for bit-wise ANDing said aligned, multi-bit block of said debug data with a multi-bit inc mask signal.

7. (Currently Amended) The increment/decrement circuit as recited in claim 1, wherein said first mask circuit comprises:

an XOR block having a plurality of XOR gates for bit-wise XORing said <u>aligned</u>, <u>multi-bit</u> block of said debug data with a multi-bit inc_invert signal to generate a multi-bit output signal; and

an AND block having a plurality of 2-input AND gates for bit-wise ANDing said multi-bit output signal with a multi-bit inc mask signal.

- 8. (Original) The increment/decrement circuit as recited in claim 1, wherein said accumulation circuit comprises:
- a first population count circuit coupled to said first mask circuit;
- a second population count circuit coupled to said second mask circuit; and

an adder circuit coupled to said first population count circuit and said second population count circuit.

- 9. (Original) The increment/decrement circuit as recited in claim 1, wherein said accumulation circuit comprises:
- a first population count circuit coupled to said first mask circuit;
- a second population count circuit coupled to said second mask circuit; and
- a subtract circuit coupled to said first population count circuit and said second population count circuit.
- 10. (Original) The increment/decrement circuit as recited in claim 1, wherein said accumulation circuit is operable to forward a signal indicative of an instantaneous outstanding transaction count based on outputs provided by said first and second mask circuits.
- 11. (Original) The increment/decrement circuit as recited in claim 10, wherein said instantaneous outstanding transaction count is forwarded to a counter circuit for further processing.

12-17. (Cancelled)

18. (Currently Amended) A computer system having an increment/ decrement circuit for use with a general purpose performance counter ("GPPC") connected to a bus carrying debug data, the increment/decrement circuit comprising:

means for receiving and aligning at least a <u>multi-bit</u> block of said debug data;

means for selectively asserting an increment signal based on selecting a first portion of said block of aligned debug data;

means for selectively asserting a decrement signal based on selecting a second portion of said block of aligned debug data; and

means for generating an accumulated value <u>using said first</u>

<u>portion and said second portion.</u> based on said increment and decrement signals.

19. (Currently Amended) The computer system as recited in claim 18, wherein said means for generating an accumulated value is operable to forward a signal indicative of an instantaneous outstanding transaction count based on said <u>first portion and said second portion</u>. increment and decrement signals.

20. (Original) The computer system as recited in claim 19, wherein said instantaneous outstanding transaction count is forwarded to a counter circuit for further processing relative to operations selected from the group consisting of latency calculations, advanced triggering, debug calculations, coverage calculations, and performance analysis.